



RX218

SUB-woofer

Loudspeaker

超低音音箱

SPECIFICATIONS (规格)

Frequency Response 频响	30 Hz - 150 Hz
Sensitivity 灵敏度	102dB SPL (1W @ 1m)
Nominal Impedance 阻抗	4 ohms
Power Handling 功率	1000 watts (rms额定), 2000 watts (peak峰值)
Maximum SPL 最大声压	130dB
Enclosure Construction 箱体	18 mm birch plywood with structured(18mm桦木夹板)
Finish 表面	Wear-resistant textured black paint (黑色耐磨粗点喷漆)
Grille 面罩	Powder coated perforated steel, foam backed(铁网、内贴透气棉)
Options 其它	1 x Integral pole mount socket (支撑座)
Input Connectors 连接器	Speakon NL4 x 2
Dimensions 尺寸 (H x W x D)	560 mm x 1066 mm x 780 mm
Net Weight 重量	67 kg

DRIVERS (驱动器)

2 x 18" (460 mm) Low Frequency, 4.5" (115 mm) voice coil
 2 x 18" (460 mm) 低频, 4.5" (115 mm) 音圈

FEATURES (特性)

- 2 x 18" subwoofer
- direct shooting design
- equipped with processor
- strong LF output
- 2 x 18" 超低音设计
- 直射式辐射设计
- 配合处理器使用
- 提供强劲的低音功率输出

APPLICATIONS (适用范围)

- theatre, auditoria, multi function room, conference room, gymnasium, high-class entertainment, discotheque.
- 剧院、礼堂、多功能厅、会议室、体育场馆、高级娱乐场所、迪厅等

DESCRIPTIONS (描述)

RX218 consists of two built-in 18" high power, long-throw driver. The cabinet adopts high efficiency folded hyperbolic design, with inner pipeline expanding by stages and the Crossover Frequency can be very low. The LF can produce high efficiency power through horn, with low end frequency, make the LF output much stronger.

RX218内置两个18"大功率、长冲程驱动单元，箱体采用高效率设计，而且低频的截止频点非常低，低频输出更具有深沉、震撼的感觉。

FREQUENCY RESPONSE

(频率响应)

