



RX25)))
2-WAY Loudspeaker
二分频 音箱

RX-SERIES

SPECIFICATIONS (规格)

Frequency Response 频响	50 Hz - 16 kHz
Sensitivity 灵敏度	99 dB SPL (1W @ 1m)
Nominal Impedance 阻抗	8 ohms
Power Handling 功率	300 watts (rms额定), 600 watts (peak峰值)
Maximum SPL 最大声压	124 dB
Nominal Dispersion 指向性(可旋转)	60° horizontal (水平), 40° vertical (垂直)
Crossover Frequency 分频点	1.2 kHz
Enclosure Construction 箱壳	18 mm birch plywood with structured (18 mm 桦木夹板)
Finish 表面	Wear-resistant textured black paint (黑色耐磨粗点喷漆)
Grille 面罩	Powder coated perforated steel, foam backed (铁网、内贴透气棉)
Suspension Hardware 吊挂件	2 x 4-Position fly track (4孔吊钩)
Options 其它	1 x Integral pole mount socket (支架座)
Input Connectors 连接器	Speakon NL4 x 2
Dimensions 尺寸 (H x W x D)	514 mm x 486 mm x 420 mm
Net Weight 重量	34.5 kg

DRIVERS (驱动器)

1 x 15" (380 mm) Low Frequency
 1 x 15" (380 mm) 低音
 1" (25 mm) High Frequency
 1" (25 mm) 高音

FEATURES (特性)

- 2-way loudspeaker
- coaxial
- 二分频音箱
- 同轴设计

APPLICATIONS (适用范围)

- theatre, auditoria, multi function room, conference room, gymnasium, high-class entertainment, discotheque.
- 剧院、礼堂、多功能厅、会议室、体育场馆、高级娱乐场所、迪厅等

DESCRIPTIONS (描述)

Rx25 consists of one 15" LF loudspeaker and one 1" compress driver, built-in optimized frequency division network and HF protection device

RX25使用一个15"低频单元和一个1"压缩驱动器,内置优化设计分频网络和高音保护器。

FREQUENCY RESPONSE (频率响应)

